

XTF SERIES

Suction Pressure Regulator

XTF series suction pressure regulator is installed at the suction line of the compressor to adjust the suction pressure and prevent the excessive compressor suction pressure.



FEATURES

- ACCURATE AND ADJUSTABLE PRESSURE REGULATION
- STAINLESS STEEL VALVE BODY, CORROSION RESISTANT
- STAINLESS STEEL BELLOWS
- HIGH LIFETIME: 250,000 TIMES

GENERAL SPECIFICATION

- Applicable for all common HCFC and HFC, such as R22, R134a, R407C, R410A, R32
- Ambient temperature min./max.: -40°C~+60°C
- Medium temperature TS min./max.: -40°C~+130°C
- Relative humidity: 0 to 100% RH

TECHNICAL PARAMETERS & DIMENSIONS

Model	Kv	MOP	Factory setting pressure	Pressure regulating range	Connections ODF		Dimensions [mm]		
	[m ³ /h]	[Mpa]	[Mpa]	[Mpa]	[inch]	[mm]	A	B	C
XTF12H01	3.2	1.8Mpa	0.25	0~0.6	1/2	-	179	64	99
XTF15H01	3.2				5/8	16	179	64	99
XTF22H01	3.2				7/8	22	179	64	99
XTF28H01	6.2				1-1/8	-	259	105	151
XTF35H01	6.2				1-3/8	35	259	105	151

